


ITALIA™ High Performance Paint Booth

The ITALIA™ is Accudraft's flagship downdraft unit designed for high production. High efficiency features and outstanding air filtration provide clean jobs and low operating costs. Rugged structural build & heavy-duty controls will provide decades of non-stop daily operation and maximize return on investment.


















Workspace

Starting Dimensions

- Interior 23' 8" long x 13' wide x 9' high
- Exterior 24' long x 13' 4 1/4" wide x 11' 6" high

Available Configurations

- Pitted Downdraft
- Raised Downdraft (Basement & Ramp)
- Semi Down

Construction

- Dual Skin 20 Gauge Insulated Electrogalvanized Steel Walls
- Simple Joint Tongue and Groove
- Textured Exterior Vinyl Coating
- UltraWhite™ Vinyl Coated Interior
- Hinged EZ-Clip Ceiling Filters
- Powder Coated Ceiling Supports
- Full Width Ceiling Filtration

Main Doors

- Opening: 9' wide x 8'11" high
- Dual Skin Insulated Vinyl Coated
- Integrated Locking Mechanism
- Wire-mesh Reinforced Windows
- Welded Steel Reinforcement Frame

Service Door

- Side Access Door with Window
- -36" wide x 82 1/2" high

Filtration

- Pre Filter Bags
 - Cleans Incoming Air
- Ceiling Filters (5 micron)
 - Down to 1/25,000 of an inch
- Floor Filter
 - Paint Arrestor (Over 98% Removal Efficiency)
- Exhaust Post Filtration
 - 2 Stage Exhaust Filtration
 Eliminates Overspray & Protects
 Exhaust Turbine

Lighting

- 48" Daylight Corrected Light Fixtures
- Inside Access Hinged Glass Doors
- Class 1 Division 2 Rated

Options

- Length Extensions, Width Extensions, Height Extensions, Drive Through, Raised Floor, Fourth Main Door, Single Phase, Side Loader, Outdoors, Overhead Mechanicals, Observation Windows

Mechanical Group

Intake

- Timeless™ Direct Drive 10HP
- 14.000 CFM
- Direct Drive Backward Inclined Turbine
- 10 HP 3 Phase High Efficiency Motor
- 1,200,000 BTU (Capable)
- 98% Efficient Direct Fire Gas or Propane Burner
- 30:1 Turn Down for Accurate Temperature
- Full Recirculation on Bake 80%
- 2 Stage Recirculation Filtration
- Intake/Exhaust Pressure Balanced

Exhaust

- 14,000 CFM
- Direct Drive Backward Inclined Turbine
- Non Loading, Non Sparking

SmartPad™ PLC Control Panel

- Auto Pressure Control & Economy Mode
- Intellcure™ Fast Temperature Rise
- EnergySmart™ VFD's Included

Certification

- ETL Listed



Warranty

- 1 Year Bumper to Bumper

Note

 SAIMA of North America reserves the right to modify or change any of the dimensions or features without notification.

